# HAMMER & BIT MODELS Small Conventional





# Rock Drilling Hammers and Bits

Numa is the world's leading manufacturer of rock drilling products dedicated to ongoing innovation and results-oriented consistency. We've built a strong legacy of high quality, Made in the USA hammers and bits for drilling holes 3½ -50½ inches (89 -1283 mm) in diameter.

Foremost to the success of our customers is Numa's personal service and technological expertise.

We work with drillers on job sites around the world to support our products and gain first-hand insight for advancing rock drilling product design to satisfy every drilling environment.



**Drilling Products** 



**Global Drilling Industries** 



Patriot. 6

k

Patents & More Pending



120m

Feet Drilled



**Countries Served** 



Years of Experience





### **SMALL HAMMERS AND BITS**

Drills holes from 3 1/2" to 10" (89 - 254 mm)

- Twelve hammer models designed for unique applications
- Hundreds of bit configurations for diverse drilling conditions
- Built for longevity and fast penetration rate
- Drill at high frequency and requires minimal air
- Exceptional performance against high heads of water
- Easy maintenance due to only 8 major hammer parts

## **DTH PRODUCTS BUILT FOR YOUR NEEDS**

Numa provides unparalleled customer support before, during and after your drilling project. Our years of experience working directly with customers on job sites means we consider your needs for every product we design. Some of the many benefits Numa customers enjoy from our Small Hammer & Bit models include:

- Mining & Quarry: Reliable performance in various formations and conditions
- > Water Well: Consistent and fast drilling, day in and day out
- 🔶 Oil & Gas: Tough, dependable, proven deep hole drilling
- Construction: Configurable designs for specific needs
- > Geothermal: Fast penetration rates in deep, hot drilling applications
- Horizontal: Efficient hard rock borehole drilling
- And many more...

# The Ultimate Rock Drilling Technology

Join the growing list of Numa customers experiencing the highest value in products, performance, and service in the drilling industry.

- Designs based upon 40+ years of experience with drillers
- Made in the USA quality and dependability
- Onsite and remote technical and product support
- Configurable designs for every drilling need
- Dedicated, in-house engineering team
- Fully tested products that come with Numa's Quality Test Certificate

#### **Other Ultimate Numa Products**

- Large Hammers and Bits
- Reverse Circulation Hammers & Bits
- HDD Drilling Systems
- Super Jaws<sup>®</sup> Overburden Drilling Systems
- Impact Ring Bits
- Retainers
- Lubrication Systems & Enviro Lube

# Hammer & Bit Specification Charts

# DTH HAMMERS Small Conventional Hammer Models

Hammer	Bit Shank	Hole Sizes		Diameter		Bore		Stroke		Weight		Length Shoulder to Shoulder		Length Shoulder to Bit Face		Thread	Min Oil Required	Blows/Min		
		inch	mm	inch	mm	inch	mm	inch	mm	lbs	kg	Inch	mm	inch mm		Connection	Quart/Hour	psi	bar	
Patriot 35A	3.5	3 ½ to 4 1/8	89 to 105	3 1/8	79	2.5	63.5	3.1	79.4	44	20	28.6	727.1	31.1	790.6	2 ¾ API Reg Pin	1	1750 @ 350	1750 @ 24	
Patriot 40	340A	4 ¼ to 5 ¼	108 to 133	3 3⁄4	95	3.1	77.5	4.0	101.6	78	35	36.1	917.6	39.4	1000.1	2 ¾ API Reg Pin	1	1960 @ 350	1960 @ 24	
Patriot 40HD	340A	4 ¼ to 5 ¼	108 to 133	3 1/8	98	3.1	77.5	4.0	101.6	89	40	36.1	917.6	39.4	1000.1	2 ¾ API Reg Pin	1	1960 @ 350	1960 @ 24	
DCS5	QL50	5 ½ to 6 1/8	140 to 156	4 1/8	124	4.0	101.6	3.0	76.2	138	63	36.4	925.5	40.1	1019.2	3 1⁄2 API Reg Pin	2	2050 @ 350	2050 @ 24	
DCS5HD	QL50	5 ¾ to 6 ¼	146 to 159	5	127	4.0	101.6	3.0	76.2	165	75	36.4	925.5	40.1	1019.2	3 ½ API Reg Pin	2	2050 @ 350	2050 @ 24	
Patriot 50	QL50	5 ½ to 6 1/8	140 to 156	4 1/8	124	4.0	101.6	3.5	88.9	140	64	36.4	925.5	40.1	1019.2	3 ⅓ API Reg Pin	2	1950 @ 350	1950 @ 24	
Patriot 60	QL60	6 to 8 ¾	152 to 222	5 1/2	140	4.5	114.3	4.0	101.6	184	84	38.8	985.5	43.2	1097.3	3 ¼ API Reg Pin	2	1950 @ 350	1950 @ 24	
Patriot 60HD	QL60	6 ¼ to 8 ¾	159 to 222	5 ¾	146	4.5	114.3	4.0	101.6	196	89	38.8	985.5	43.2	1097.3	3 ½ API Reg Pin	2	1950 @ 350	1950 @ 24	
Patriot 60W	360	6 to 8 ¾	152 to 222	5 1/2	140	4.5	114.3	4.0	101.6	204	93	43.2	1097.0	44.8	1138.2	3 ½ API Reg Pin	2	1800 @ 350	1800 @ 24	
Patriot 80	380	7 % to 10	200 to 254	7 1/8	181	6.0	152.4	3.8	95.3	364	165	45.1	1146.2	49.9	1266.8	4 ½ API Reg Pin	3	1850 @ 350	1850 @ 24	
Patriot 85	380	7 % to 10	200 to 254	7 1⁄8	181	6.0	152.4	3.8	95.3	419	190	52	1320.8	57.3	1455.4	4 ½ API Reg Pin	3	1850 @ 350	1850 @ 24	
Patriot 85Q	QL80	7 ½ to 10	200 to 254	7 1/8	181	6.0	152.4	3.8	95.3	406	185	51.2	1300.5	56.0	1422.5	4 ½ API Reg Pin	3	1850 @ 350	1850 @ 24	

# DTH BITS Small Conventional Bit Models

DTH B	ITS Sr	mall Con	ventiona	l Bit Moo	lels					S = Stan	dard	C	<b>)</b> = <b>O</b>	ption	al	
Size Class	Bit Shank	Diamet	er Hole	We	ight	Air		Face		Gauge		Ca	rbide S	ize		
Size Class	BICSNANK	inch	mm	lbs	kgs	Slots	CC	c٧	F	Buttons	7/16"	9/16"	5/8"	3/4"	7/8"	
3" Class	3.5	3 ½ to 4 1/8	89 to 105	14 to 15	6 to 7	2		S	S	8	S					
4" Class	340A	4 ¼ to 5 ¼	108 to 133	18 to 22	8 to 10	2 or 3	S	S	S	8		S	0			
	TD40	4 ¼ to 5 ¼	108 to 133	21 to 24	10 to 11	2 or 3	S	S	S	8		S	0			
5" Class	QL50	5 ½ to 6 1/8	140 to 156	33 to 36	15 to 16	2 or 3	S	S	S	8 or 10			S	0		
6" Class	360	6 to 6 ¾	152 to 171	52 to 55	24 to 25	2	S	S	S	8, 9 or 10			S	0		
	360	7 to 8 ¾	178 to 222	63 to 76	29 to 34	3	S		S	9			S	0		
	QL60	6 to 6 ¾	152 to 171	52 to 55	24 to 25	2 or 3	S	S	S	8, 9 or 10			S	0		
	QL60	7 to 8 ¾	178 to 222	63 to 76	29 to 34	3	S		S	9			S	0		
8" Class	380	7 % to 10	200 to 254	106 to 125	48 to 57	3	S			12				S	0	
	QL80	7 % to 10	200 to 254	107 to 127	49 to 58	3	S			12				s	0	

**FLAT** 

Provides good



performance in medium to hard formations. The strongest face design producing durable, long lasting drilling.



#### **CONCAVE**

Provides consistent drilling in all formations. The cone shaped depression in the face has piloting effect to drill straighter holes.



#### **CONVEX**

Provides fast penetration rates in hard and abrasive formations. Face design allows for increased body support for gauge carbide.



# **SPHERICAL**

Provides best overall performance in granite hard rock and granite formations. Known as the strongest carbide for deep hole drilling.



Diamond	Wear Protection	Retained					
0	0						
0	0						
0	0	0					
0	0	0					
0	0						
0	0	0					
0	0						
0	0	0					
0	0	0					

# BALLISTIC

Provides fastest penetration rates in soft/medium, less abrasive formations. Produces larger spoils/cuttings.



### **DOUBLE DOME**

Provides best performance in limestone and sandstone formations. Much stronger than ballistic and still performs when not sharpened.



The World's Leading Rock Drilling Products

860.923.9551 www.numahammers.com

> 646 Thompson Rd PO Box 348 Thompson, CT 06277 USA



