


FEATURES

- Outdistances competitive hammers in both speed and longevity
- Simplified hammer design with less internal components
- Drills at high frequency to provide less vibration and smooth operation
- More efficient design requires less air which equals fuel savings
- Less overall parts promote easier maintenance
- Designed to operate at pressures up to 250 PSI (17.2 BAR)
- Ability to drill efficiently against high heads of water
- Plate drive system to eliminate spline wear and galling

AIR CONSUMPTION



DRILL PRESSURE (PSI)



SPECIFICATIONS

Diameter	15-1/2"	394 mm
Bore	13-1/4"	337 mm
Stroke	4-1/2"	114 mm
Weight (Hammer only)	2523 lbs.	1144 kg
Length (Shoulder to Shoulder)	65-15/16"	167 cm
Length (Shoulder to Bit Face)	75-15/16"	193 cm
A.P.I. Reg. Threads	8-5/8	

- 1100 blows per minute at 200 PSI (13.6 BAR)
- Drills holes from 18" to 30" (457 mm 762 mm) in diameter

2 1/2 (12.7mm) CHOKE • Accepts P180 bit shank



Down Hole Button Bits

Patriot® 180

P180 Bit Shank

DIAMETER

inches	(millimeters)
18"	(457 mm)


20"	(508 mm)
22"	(559 mm)
24"	(610 mm)
26"	(661 mm)
28"	(711 mm)
30"	(762 mm)

WEIGHT* pounds (kilograms)

	• •
1029 lbs.	(468 kg)
1254 lbs.	(570 kg)
1347 lbs.	(612 kg)
1616 lbs.	(735 kg)
1751 lbs.	(796 kg)
2007 lbs.	(912 kg)
2275 lbs.	(1034 kg

^{*} Bit weights are approximate

FACES AVAILABLE



Concave / Flat

FEATURES

- Concave or Flat face design for advanced hole cleaning capabilities
- 3/4" (19 mm), 7/8" (22 mm) and 1" (25 mm) carbide options available
- Several grades and types of carbide are available
- Significantly larger spline area for exceptional strength and transfer of torque
- Plate drive system for increased spline life
- Side wear buttons are standard on all bits
- Other bit sizes may be available upon request

For More Information Contact:

646 Thompson Road • Thompson, CT 06277 USA Phone: (860) 923-9551 • Fax: (860) 923-2617 numa@numahammers.com • www.numahammers.com

